

1885ENH

Networking Cables

Datatwist® cable

CAT 7 S/FTP LSNH

2011-01-21 v7


Applications

- Horizontal and building backbone cable
- Support current and future Category 6a and 7 applications, such as:
10GBase-T (10 Gigabit Ethernet), 1000Base-T (Gigabit Ethernet), 100 Base-T, 10 Base-T, FDDI, ATM

General standards

- International standard: ISO/IEC 11801 2nd edition (2002) and ISO/IEC 11801 Amendment 2 (2010)
- European standard: EN 50173-1 (2002) and EN 50173-1 Amendment 1 (2009)

Construction & Dimensions



- | | |
|----------------------------------|---|
| 1. Conductor | |
| Material | Solid bare copper ETP |
| Diameter | AWG 23 |
| 2. Insulation | |
| Material | Foamed polyethylene |
| Nominal diameter over insulation | 1.45 mm |
| 3. Cable core | |
| Pair | 2 twisted insulated conductors with overall foil |
| Foil | Laminated aluminium-polyester
Aluminium facing outside |
| Number of shielded pairs | 4, all twisted together |
| Colour code pair 1 | White / Blue |
| Colour code pair 2 | White / Orange |
| Colour code pair 3 | White / Green |
| Colour code pair 4 | White / Brown |
| 4. Braid | |
| Material | Solid tinned copper |
| Coverage | ≥ 30% |

5. Jacket

Material	LSNH
Diameter	7.2 ± 0.3 mm
Ripcord	Nylon ripcord under jacket

Electrical characteristics

Reference standard : ISO/IEC 61156-5 edition 2.0 (2009)

Low frequency and D.C. (at 20 °C)	Specification	Unit
D.C. resistance conductor	< 9,5	Ω/100m
Resistance unbalance: within a pair / between pairs	< 2 / < 4	%
Insulation resistance	≥ 5000	MΩ.km
Dielectric strength conductor-conductor and conductor-screen (2 sec.)	2.5	kV DC
Mutual capacitance	< 56	nF/km
Capacitance unbalance pair to ground	< 1600	pF/km
Nominal velocity of propagation (for information only)	0.78	c
Delay skew (differential delay)	≤ 25	ns/100m
Transfer impedance according IEC 61156-5	Grade 2	
Coupling attenuation according IEC 61156-5	Type II	

High frequency (at 20 °)														
TYPE	1*	4	10	16	31.2	62.5	100	125	200	250	300	600	1000*	MHz
Attenuation	2.0	3.7	5.9	7.4	10.4	14.9	19.0	21.4	27.5	31.0	34.2	50.1	66.9	dB/100m
NEXT	78.0	78.0	78.0	78.0	78.0	75.5	72.4	70.9	67.9	66.4	65.2	60.7	57.4	dB/100m
PS NEXT	75.0	75.0	75.0	75.0	75.0	72.5	69.4	67.9	64.9	63.4	62.2	57.7	54.4	dB/100m
ACR	76.0	74.3	72.1	70.6	67.6	60.6	53.4	49.6	40.4	35.5	31.1	10.6	-9.5	dB/100m
PS ACR	73.0	71.3	69.1	67.6	64.6	57.6	50.4	46.6	37.4	32.5	28.1	7.6	-12.5	dB/100m
ACR-F	78.0	78.0	75.3	71.2	65.4	59.4	55.3	53.4	49.3	47.3	45.8	39.7	35.3	dB/100m
PS ACR-F	75.0	75.0	72.3	68.2	62.4	56.4	52.3	50.4	46.3	44.3	42.8	36.7	32.3	dB/100m
Return Loss	20.0	23.0	25.0	25.0	23.6	21.5	20.1	19.4	18.0	17.3	17.3	17.3	15.1	dB/100m
TCL level 1	40.0	34.0	30.0	28.0	25.1	22.0	20.0	19.0	17.0	16.0				dB/100m
EL TCTL	35.0	23.0	15.0	10.9	5.1									dB/100m
Impedance upper limit	122.2	115.2	111.9	111.9	114.1	118.3	121.9	123.9	128.8	131.5	131.6	131.6	142.8	Ω
Impedance lower limit	81.8	86.8	89.4	89.4	87.7	84.5	82.0	80.7	77.6	76.0	76.0	76.0	70.0	Ω
Propagation delay	570	552	545	543	540	539	538	537	536	536	536	535	535	ns/100m

NOTE: Limits below 4MHz are for information only. Values at 1000 MHz are for information only.

Mechanical characteristics

	Specification	Unit
Elongation at break of the conductors	8	%
Minimum elongation at break of the insulation	≥ 100	%
Minimum elongation at break of the sheath	≥ 100	%
Tensile strength of sheath	> 9	MPa

Environmental and overall characteristics

	Specification	Unit
Maximum operating voltage (for all temperatures cable is intended to be used)	72	V D.C.
Maximum continuous current per conductor (@25°C)	1.5	A
Temperature rating installation	0 / 50	°C
Temperature rating operation	- 30 / 60	°C
Total cable weight	52	kg/km
Minimum bending radius (during operation and installation)	29 / 58	mm
Maximum pulling strength	85	N
Burning load	500	kJ/m
Smoke density acc. to IEC 61034-1/2 & EN50268-1/2; transmittance	> 60	%
Amount of halogen acid gas acc. to IEC 60754-1/2 & EN50267-1/2; pH	> 4.3	
Amount of halogen acid gas acc. to IEC 60754-1/2 & EN50267-1/2; Conductivity	< 10	µS/mm
Fire performance according IEC 60332-1	Pass	



Belden declares this product to be in compliance with the environmental regulations EU RoHS (Directive 2002/95/EC, 27 January 2003); this is valid for all material produced after the RoHS compliant date for this product.